










C.H. ROBINSON

CONTRACT FLATBED EQUIPMENT GUIDE

Use this guide to compare the different types of flatbed equipment. Explore each trailer's capabilities and determine what is right for your unique freight. Once you've identified the right equipment, visit www.chrobinson.com to learn more, request a quote, and get your freight on the road.

	MAXIMUM FREIGHT DIMENSIONS				TRAILER SPECIFICATIONS		
	WEIGHT/ CAPACITY	TOP DECK (TD)	MAIN DECK (MD)	REAR DECK (RD)	LENGTH (L)	WIDTH (W)	HEIGHT (H)
Legal Flatbed Trailer 	45–48,000 lbs.	N/A	50'L x 8.5'W x 8.5'H	N/A	48'	8.5'	5'
Legal Step Trailer (<i>Single Drop</i>) 	43–46,000 lbs.	10'L x 8.5'W x 8.5'H	38'L x 8.5'W x 10'2"H	N/A	48'	8.5'	TD = 5' MD = 3'4"
Double Drop Trailer (<i>Low Boy</i>) 	38–40,000 lbs.	10'L x 8.5'W x 8.5'H	28'L x 8.5'W x 11'6"H	10'L x 8.5'W x 10'2"H	48'	8.5'	TD = 5' MD = 1'8" RD = 3'4"
Removable Goose Neck Trailer (<i>RGN</i>) 	38–40,000 lbs.	N/A	28'L x 8.5'W x 11'6"H	10'L x 8.5'W x 10'2"H	48'	8.5'	MD = 1'8" RD = 3'4"
Stretch Flatbed Trailer 	45,000 lbs.	N/A	48–80'L x 8.5'W x 8.5'H	N/A	45–80'	8.5'	5'
Stretch Single-Drop Deck Trailer 	43,000 lbs.	10'L x 8.5'W x 8.5'H	38–63'L x 8.5'W x 10'2" H	N/A	48–63'	8.5'	TD = 5' MD = 3'4"
Stretch Double-Drop Deck Trailer (2 or 3 axles depending on weight) 	40,000 lbs.	10'L x 8.5'W x 8.5'H	28–50'L x 8.5'W x 11'6" H	10'L x 8.5'W x 10'2"H	48–70'	8.5'	TD = 5' MD = 1'8" RD = 3'4"

Trailers vary depending on the load requirements and state regulations. These are standard equipment dimensions (these dimensions provided for general information purposes only). Permits may still be required for your freight, but regulations vary from state to state. Please contact your C.H. Robinson flatbed representative for assistance with your load permit requirements at 1-800-323-7587 or email solutions@chrobinson.com. ©2015 C.H. Robinson Worldwide, Inc. All Rights Reserved.





C.H. ROBINSON

CONTRACT FLATBED EQUIPMENT GUIDE

FLATBED TARPS



Tarps are available in several sizes to accommodate different sized loads. The most common tarp sizes are 4', 6', and 8' long. Determining the right tarp for your freight depends on which portion of the freight needs to be covered. Explore your options and decide what will work for your needs.

Smoke Tarps: cover the front portion of a load

Top Tarps: cover the top of the load

Steel Tarps: 4' or 5' drop tarps

Lumber Tarps: 6'-8' drop tarps, (a.k.a. full tarps)

	MATERIAL	WEATHER PROTECTION	DIMENSIONS	TIE-DOWN PLACEMENTS	MAXIMUM WEIGHT	OTHER FEATURES
4' Drop Steel Tarps 	18 oz. black vinyl coated fabric	Water resistant	16'L x 24'6"H	Grommets and dee rings 30" on center	63 lbs. each	Requires two tarps for a full set
Standard 6' Tarps 	18 oz. black vinyl coated fabric	Water resistant	24'L x 26'H Tail 6'L 6'H	Grommets and dee rings 30" on center	103 lbs. each	6' drops For trailers up to 48'

Trailers vary depending on the load requirements and state regulations. These are standard equipment dimensions (these dimensions provided for general information purposes only). Permits may still be required for your freight, but regulations vary from state to state. Please contact your C.H. Robinson flatbed representative for assistance with your load permit requirements at 1-800-323-7587 or email solutions@chrobinson.com. ©2015 C.H. Robinson Worldwide, Inc. All Rights Reserved.